

**EnovaNxt instrument cable  
1x0.22mm<sup>2</sup>, 1/4" mono straight  
plug to 1/4" mono 100° Relax An-  
gle plug with True Mold Technol-  
ogy**

Art. number: **NXT-I2-PLMM2-\***



**GENERAL DATA**

Brand:	EnovaNxt
Series:	I2
Cable type:	Instrument cable
Connector type:	1/4" mono to 1/4" mono 100° angled
Country of origin:	EU

**CABLE CONSTRUCTION**

Conductor:	Copper wires tinned 28 x 0.10mm	Core insulation:	Foam-skin-PE 1.9mm with semi-conductive PVC layer on top, 2.4mm
Conductor cross section:	0.22mm <sup>2</sup> / AWG 24	Screen:	Copper spiral screen bare
Core insulation:	Foam-skin-PE 1.9mm with semi-conductive PVC layer on top, 2.4mm	Outer jacket:	PVC, soft, black matt, 5.9mm +/- 0.20mm

**ELECTRICAL CHARACTERISTICS**

Conductor resistance:	90 Ohm/km	Insulation resistance:	1 GOhm x km
Capacitance:	85 pF/m		

**MECHANICAL AND THERMAL CHARACTERISTICS**

Temperature range:	-20°C to +70°C
--------------------	----------------

**STANDARDS**

Norms:	Following VDE-norms
Halogen-free:	no
RoHS:	2011/65/EU

UV resistance:	Yes according UL 758
Flame retardant:	no
REACH:	1907/2006

**CONNECTIVITY SPEZIFICATIONS**

Connector A:	¼" plug mono, straight
Tip / Sleeve:	Brass, nickel plated
Tip design:	Tip shape suitable for US, Europe and Japan standards
Insulator:	PA66
Strain relief:	360°, zinc-die cast, crimped
Lifetime:	> 1000 mating cycles

Connector B:	¼" plug mono, 100° Relax Angle
Tip / Sleeve:	Brass, nickel plated
Tip design:	Tip shape suitable for US, Europe and Japan standards
Insulator:	PA66
Strain relief:	360°, zinc-die cast, crimped
Lifetime:	> 1000 mating cycles